

FURUTECH

PURE TRANSMISSION

*One piece wound-wire conductor
construction Binding Post*

*Premier Performance and
Legendary Build Quality*



FT-865(G)

FT-865(R)

***Furutech One piece Wound-Wire conductor
Long Binding Posts series***

All audiophiles search for the same qualities: Verisimilitude to the original event, a sense of engagement promoting suspension of disbelief, a visceral immersion in the audio video experience. They also know that everything in the signal path makes a difference, and that includes speaker binding posts.

Furutech's revolutionary, patent-pending FT-860 Series One-Piece Wire-Wound Binding Posts are ideal for speaker builders, manufacturers and do-it-yourselfers looking for low-mass, quality engineered and superb-sounding terminals. The FT-860 Series is a first in speaker terminal design: The reduced metal mass of the binding post terminal pole piece lowers impedance values improving the sound even more. It's easy enough to follow a trend like low-mass binding posts -- less is more -- but Furutech engineers weren't satisfied with merely cutting away material and moving "new" and "improved" out the door. It has to work impeccably and sound glorious. Only Furutech has the expertise of materials, engineering horsepower and advanced processing to create products like the FT-860 Series with its innovative one-piece wire-wound conductor.


The FT-865 features a one piece wound-wire Alpha-OCC conductor. This special conductor allows for reduced metal mass in the binding post terminal pole construction resulting in minimal impedance and less susceptibility to the negative effects of RFI and magnetic fields. Also the environmentally friendly construction process of the wound-wire conductor means less metal waste compared to conventional CNC, mold or pressing processes. The FT-865 series comes fitted with eutectic copper alloy housing.

Features and Materials

- Patent-pending One piece wound-wire construction
- Main conductor: Rhodium or 24k Gold plated α (Alpha)-OCC wound-wire conductor
- Housing: Eutectic copper alloy
- POM plastic injected terminal pole
- Nylon (red/white) and Polycarbonate insulation
- Connections: Disconnect connector termination
- Specified for core diameters up to 4.5mm

Patented wound-wire unit Exploded and Completed view
--


Connection: Banana Side / Spade Side / Disconnect connector termination



Connect with Fully Insulated Female Disconnect FT-210-S image
(α (Alpha) Pure copper)



Connect with Female Disconnect F250 series image (α (Alpha) Phorphos Bronze)




F210

F214

F218

Completed Terminal Pole size and Housing view :



Make a More Powerful Connection with Furutech!

FURUTECH CO., LTD • service@furutech.com • www.furutech.com