

FURUTECH

PURE TRANSMISSION



FI-E30 NCF (R) Furutech's Ultimate SCHUKO Chassis Socket

Non-magnetic Rhodium plated Pure Copper Conductor (Type: 2-pole +earth; Rating: 16A 250V A.C.)

Nano Crystal² Formula - Nano Crystalline, Ceramic and Carbon Powder

Incorporated into select Furutech products, Nano Crystal² Formula --- NCF is comprised of a special crystalline material that has two "active" properties. First, it generates negative ions that eliminate static and secondly, it converts thermal energy into far-infrared. Furutech then combines this remarkable crystalline material with nano-sized ceramic particles and carbon powder for their additional "Piezo Effect" damping properties. The resulting Nano Crystal² Formula is the ultimate electrical and mechanical damping material – only found in Furutech products!



Features

- Main conductors: α (Alpha) Pure copper Rhodium plated
- Dimensions: 50.6mm × 50.6mm × 36.0mm (L×W×H)
- Insulation Materials: Nylon/fiberglass incorporating special "NCF" anti-resonance damping material - nano-sized crystalline, piezo ceramic particles and carbon powder

All metallic parts are treated by FURUTECH α (Alpha) Process (Super Cryogenic & Demagnetize Treatment)

FURUTECH CO., LTD.
service@furutech.com

Product name	Product Introduction	JAN CODE
FI-E30 NCF (R)	SCHUKO Socket	