

FURUTECH

PURE TRANSMISSION

AEx

オーディオ銘機賞

Audio Excellence Award 2008



Evolution II Speaker

High End Speaker Cable



Furutech's Evolution Series was awarded The Absolute Sound Editors' Choice Award in both 2007 and 2008



Evolution II Speaker-04 • 2 meter

Evolution II Speaker-06 • 3 meter

Features:

- Beautifully engineered speaker cables featuring α (Alpha) μ -OFC Conductors around a center PE core to minimize transmission loss
- Insulated with special formula polyethylene to reduce capacitance
- Finished with High Performance FP-218 (G) Spade Connectors or FP-202 (G) Banana Connectors
- FP-218 (G) Spade Connector: 24k gold-plated nonmagnetic pure-copper α (Alpha) conductor
- FP-202 (G) Banana Connector: 24k gold-plated nonmagnetic eutectic cast copper alloy α (Alpha) conductor
- Results in greater resolution, clarity, powerful dynamics, and an ultra-quiet soundstage in which music develops more fully without artificial upper-frequency "presence region" glare

α (Alpha) Conductor Is Composed Of Fine μ -OFC Wire Strands

Treated With Furutech's α (Alpha) Cryogenic and Demagnetizing Process

Here's What The Critics Say

"My first overall impression [of the Evolution cables] was one of control. ...It was as though I could feel that there was something holding the music firmly within

its grasp and allowing the system to reproduce more effectively the intensity, fabric and overall visceral impact that one might expect in a live environment.

“The sound I heard was simply put spectacular. The system’s ability to take the intensity of the music and blend it with the subtle nuances of particularly difficult passages allowed for a listening experience that I am somewhat unaccustomed to hearing from my system in general.

“... Extremely lifelike and palpable without being overly dominate or forward sounding. ... The noise floor was lowered and I was able to hear a rich harmony of musical instruments that did not overwhelm the passage with excess noise or distortion.

“ ... wholeheartedly recommend these cables to someone looking for more from their present system.”

-- Brett Rudolph, [Enjoy the Music.com](http://EnjoytheMusic.com)[®]

Specifications: Construction and Materials

- 6 bundles 20-strand α (Alpha) μ -OFC Conductor · 0.18mm, 2.81mm diameter
- Insulation: Special polyethylene (Red/White) 5.1mm diameter
- Cable Lay: Two cores twisted together with cotton yarn
- Sheath: RoHS Compliant flexible PVC (Dark Green) 13.5mm diameter
- Jacket: Nylon yarn braid approx. 14.5mm
- Connectors FP-218 (G) spade or FP-202(G) Banana

Electrical Properties of Cable		Test Method
Max. Conductor Resistance	5.4 Ω/km	JISC3005 6 20 C
Min. Insulation Resistance	1000 MΩ · km	JISC3005 9.1 20 C
Dielectric Strength	AC. 1000 V/1 min.	JISC3005 8
Electrostatic Capacitance	Approx 48.2 PF/m	at 1 KHz

FURUTECH CO., LTD.
service@furutech.com

All metallic parts are treated with the

**FURUTECH α (Alpha) Process (Super Cryogenic & Demagnetizing Treatment.)*

***Make A More Powerful Connection With Furutech
Pure Transmission Technology***