FURUTECH
PURE TRANSMISSION

AEx
オーディオ銘機賞
Audio Excellence Award 2008

BEST OF INNOVATIONS 2009 — INNOVATIONS INTERNATIONAL CES

the absolute sound 2008 EDITORS' CHOICE AWARD WINNER

2007 the absolute sound Product of the Year Awards

BLUEMOON AWARD — sixmoons.com

Enjoy the Music.com Best Of 2007 Award

High End Performance XLR Connectors

FP-601M(R) *FP-602F(R)*

FP-601 M(R) (Male) Non-magnetic Rhodium plated Conductor

Features:

- ***α*** *(Alpha)* Beryllium copper and phosphor bronze Conductor
- Copper alloy body with PVDF Teflon insulation
- Connections: Soldered
- Specified for cable diameters up to 12mm
- Dimensions:
  19.5mm ± 0.1 diameter x 48.5mm ± 0.1mm overall length

FP-602 F(R) (Female) Non-magnetic Rhodium plated Conductor

Features:

- ***α*** *(Alpha)* Beryllium copper and phosphor bronze Conductor
- Copper alloy body with PVDF Teflon insulation
- Connections: Soldered
- Specified for cable diameters up to 12mm
- Dimensions:
  19.5mm ± 0.1 diameter x 54.2mm ± 0.1mm overall length

All metallic parts are treated with the

FURUTECH α (Alpha) Process (Super Cryogenic & Demagnetizing Treatment)

FURUTECH CO., LTD. **service@furutech.com**

Make A More Powerful Connection with Furutech!